





























ITEM	PHOTO	Description	Frequency
ST-VGT TCP/IP KIT		<p>TCP/IP/GSM/PSTN/RFID NEW</p> <p>Wired & wireless compatible alarm control panel GSM+TCP/IP KIT, Touch keypad New features: 1. Built-in TCP/IP module 2. Apps available for Android and IOS, download "STPanel" at app store for iPhone. Control your system via your smart phone APP from anywhere in the world. 3. Support remotely upgrade to latest software from IE interface 4. Receive push notifications of the activated room and emails direct to your smart phone. 5. PGM output 6. Easily Customized language French/Spanish/or others at IE interface Traditional features: 1. Voice indication for operation, LCD display, Support 8 remote controllers 2. Built-in GSM module, remote control by SMS, SMS notification 3. 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers 4. Rechargeable battery backup 11.1V/1000mA, 512 event log 5. GSM frequency 850/900/1800/1900MHZ 6. GSM/TCP/IP auto switch 7. The Kit includes: 1x panel; 1x PIR; 1x door contact MD210R; 2 x remote controller PB403R; 1PCS power supply 15V/2A</p>	433/868
ST-VB GSM KIT		<p>GSM/PSTN</p> <p>Wired & wireless compatible alarm control panel GSM+PSTN KIT, Touch keypad New features: 1. Built-in SD Card Slot, Support local update from SD Card 2. GSM with intercom function 3. Sleep Mode, 4. PGM output 5. Listen-in time 0s-255s optional, AC loss/landline disconnect inspection disable/enable 6. 16 User codes 7. SMS/Phone notification optional Traditional features: 1. Voice indication for operation, LCD display, Support 8 remote controllers 2. Built-in GSM module, remote control by SMS, SMS notification 3. 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers 4. Rechargeable battery backup 11.1V/1000mA, 120 event log 5. GSM frequency 850/900/1800/1900MHZ 6. GSM/PSTN auto switch 7. The Kit includes: 1x panel; 1x PIR; 1x door contact MD210R; 2 x remote controller PB403R; 1PCS power supply 15V/2A</p>	433/868
ST-VB PSTN KIT		<p>GSM/PSTN</p> <p>Wired & wireless compatible alarm control panel GSM+PSTN KIT New features: 1. Built-in SD Card Slot, Support local update from SD Card 2. GSM with intercom function 3. Sleep Mode, 4. PGM output 5. Listen-in time 0s-255s optional, AC loss/landline disconnect inspection disable/enable 6. 16 User codes 7. SMS/Phone notification optional Traditional features: 1. Voice indication for operation, LCD display, Support 8 remote controllers 2. Built-in GSM module, remote control by SMS, SMS notification 3. 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers 4. Rechargeable battery backup 11.1V/1000mA, 120 event log 5. GSM frequency 850/900/1800/1900MHZ 6. GSM/PSTN auto switch 7. The Kit includes: 1x panel; 1x PIR; 1x door contact MD210R; 2 x remote controller PB403R; 1PCS power supply 15V/2A</p>	433/868
ST-V GSM+PSTN KIT		<p>GSM/PSTN</p> <p>Wired & wireless compatible alarm control panel GSM+PSTN KIT New features: 1. Voice indication for operation, LCD display, Support 8 remote controllers 2. Built-in GSM module, remote control by SMS, SMS notification 3. 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers 4. Rechargeable battery backup 11.1V/1000mA, 120 event log 5. GSM frequency 850/900/1800/1900MHZ 6. GSM/PSTN auto switch 7. This Kit includes: 1PCS control panel; 1PCS PIR; 1 PCS magnetic contact MD210R; 2PCS remote controller PB403R; 1PCS power supply 15V/2A</p>	433/868
ST-IVB GSM KIT		<p>GSM/PSTN</p> <p>Wired & wireless compatible alarm control panel GSM+PSTN KIT FULL TOUCH SCREEN New features: 1. Voice indication for operation, LCD display, Support 8 remote controllers 2. Built-in GSM module, remote control by SMS, SMS notification 3. 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers 4. Rechargeable battery backup 11.1V/1000mA, 120 event log 5. GSM frequency 850/900/1800/1900MHZ 6. GSM/PSTN auto switch 7. This Kit includes: 1PCS control panel; 1PCS PIR; 1 PCS magnetic contact MD210R; 2PCS remote controller PB403R; 1PCS power supply 15V/2A</p>	433/868
ST-IVB PSTN KIT		<p>GSM/PSTN</p> <p>Wired & wireless compatible alarm control panel GSM+PSTN KIT FULL TOUCH SCREEN New features: 1. Voice indication for operation, LCD display, Support 8 remote controllers 2. Built-in GSM module, remote control by SMS, SMS notification 3. 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers 4. Rechargeable battery backup 11.1V/1000mA, 120 event log 5. GSM frequency 850/900/1800/1900MHZ 6. GSM/PSTN auto switch 7. This Kit includes: 1PCS control panel; 1PCS PIR; 1 PCS magnetic contact MD210R; 2PCS remote controller PB403R; 1PCS power supply 15V/2A</p>	433/868

ITEM	PHOTO	Description	Frequency
ST-IV GSM KIT		GSM/PSTN	433/868
ST-IV PSTN KIT		<p>Wired & wireless compatible alarm control panel</p> <p>GSM+PSTN KIT</p> <ol style="list-style-type: none"> Voice indication for operation, LCD display, Support 8 remote controllers Built-in GSM module, remote control by SMS, SMS notification 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers Rechargeable battery backup 11.1V/1000mA, 120 event log GSM frequency 850/900/1800/1900MHZ GSM/PSTN auto switch This Kit includes: <ul style="list-style-type: none"> 1 pcs control panel; 1 PCS PIR; 1 PCS magnetic contact MD210R; 2 PCS remote controller PB403R; 1 PCS power supply 15V/2A 	
ST-III B GSM KIT		GSM/PSTN	433/868
ST-III B PSTN KIT		<p>Wired & wireless compatible alarm control panel</p> <p>GSM+PSTN KIT, Touch keypad</p> <p>New features:</p> <ol style="list-style-type: none"> Built-in SD Card Slot, Support local update from SD Card GSM with intercom function Sleep Mode, PGM output Listen-in time 0s~255s optional, AC loss/land line disconnect inspection disable/enable 16 User codes SMS/Phone notification optional <p>Traditional features:</p> <ol style="list-style-type: none"> Voice indication for operation, LCD display, Support 8 remote controllers Built-in GSM module, remote control by SMS, SMS notification 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers Rechargeable battery backup 11.1V/1000mA, 120 event log GSM frequency 850/900/1800/1900MHZ GSM/PSTN auto switch This Kit includes: 1x panel; 1x PIR; 1x door contact MD210R; 2x remote controller PB403R; 1 PCS power supply 15V/2A 	
FC-300 PSTN KIT		PSTN	433
ST-III KIT		<p>Wired & wireless compatible alarm control panel</p> <p>PSTN KIT</p> <ol style="list-style-type: none"> Voice indication for operation, LCD display, Support 8 remote controllers 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers Rechargeable battery backup 11.1V/1000mA 120 event log Electric appliance control, can work with PL208 electrical switch This Kit includes: <ul style="list-style-type: none"> 1 pcs ST-III panel; 1 PCS PIR; 1 PCS magnetic contact MD210R; 2 PCS remote controller PB403R; 1 PCS power supply 15VDC 	


ITEM	PHOTO	Description	FREQUENCY
FC-7540 TCP/IP		SAME FEATURES AS ST-VGT ABOVE BUT WITHOUT VOICE PROMPTING IN LOCAL, With Wired LCD keypad programming.	433/868
FC-7540 LCD Keypad		Wired LCD keypad for FC-7540, can connect 8 wired keypads	*
FC-7504 GSM		<ol style="list-style-type: none"> Voice indication for operation, LCD display, Support 8 remote controllers Built-in GSM module, remote control by SMS, SMS notification 8 wired 32 wireless zone, 2 CMS number (Contact ID), 4 voice numbers 150 event log GSM frequency 850/900/1800/1900 MHz GSM/PSTN auto switch 	433/868
FC-7668 GSM+PSTN		 <ol style="list-style-type: none"> Support GSM/GPRS module Support software upgrade from local SD card, Zone name edited from SD file 8 wired zones and 32 wireless zones, 128 BUS zone by single zone module, 8 partitions can be armed and disarmed separately 2 CMS number (Contact ID), 8 voice numbers Support 16 remote controllers, 10 extra keypads, 8 wireless siren, 32 wireless electric switch, PGM Output, 16 Channel Replay Output module 32 user codes, 512 event log Standard Kit includes: 1 pc panel and 1 pc LCD keypad 	433/868
FC-7668 PSTN			433/868
FC-7564 (GSM+PSTN)		 <ol style="list-style-type: none"> Support GSM/GPRS module 10-second automatic message recording 8 wired zones and 24 wireless zones, 32 BUS zone by single zone module 2 CMS number (Contact ID), 4 voice numbers Support 8 remote controllers, 8 extra keypads 1 installer code 24 user codes, 128 event log Standard Kit includes: 1 pc panel and 1 pc LCD keypad 	433/868
FC-7564 PSTN			433/868
LCD keypad		FC-7668'S LCD KEYBOARD	*
		FC-7664 LCD display keypad	*




ITEM	PHOTO	Description	FREQUENCY
FC-7601		single zone module for panel FC-7668/FC-7564	*
FC-7616DM		16 CH Relay Module For FC-7668	*
FC-7664 PSTN		<p>1, 16 wired zones and 24 wireless zones, 24 keypad zones expandable, total 64 zones, 4 partitions can be armed and disarmed separately</p> <p>2, 2 CMS number (Contact ID), 8 voice numbers, Support remote program by telephone</p> <p>3, Support 8 remote controllers, 150 event log</p> <p>4, Standard Kit includes: 1 pc panel and 1 pc LCD keypad B</p>	*
FC-7664 LCD		FC-7564'S LCD KEYBOARD	*








ITEM	Description	FREQUENCY		
EAVS-2504 (4CH) Hi3520D				
TCP/IP+PSTN	Alarm Module: DVR+ALARM 2 in 1 COMBO	433/866 (TCP/IP+PSTN)		
 1 pcs remote controller 1pcs power	Support all of our wired and wireless accessories ◎8 two way wireless or wired LCD keypad,8 remote controller,with a mouse. ◎8 wired zones, 32 wireless zones, 64 bus zones total 108 zones. ◎Overall fortification,4 partitions independent fortificaiton,stay home auto bypass. ◎Tel-line, GPRS,TCP/IP three in one network triple networking communication alarm ◎4 voice phone, 2 data phone, 2 free arm/disarm phone,SMS GPRS alarm and arm/disarm. ◎IE remote programe, IE remote upgrade, ID remote control, Contact ID protocol. ◎Voice prompt, two way intercom, spot listening, timing arm/disarm,online report. enviromental monitor and remote switch control, built-in UPS and centralized power	433/868 (TCP/IP+GPRS)		
EAVS-2508 (8CH) Hi3520D	◎Relay linkage, programmable output, built-in siren.			
 1 pcs remote controller 1pcs power	◎Support Video door phone Video module: ◎2 channel 720P+2channel 960H (EAVS-2304) ◎8 channel 960H/4 channel 720P+4channel 960H (EAVS-2308/EAVS-2508)	433/868 (TCP/IP+PSTN)	433/868 (TCP/IP+GPRS)	
EAVS-2038 (8CH) Hi 3521	◎16*D1/8D1+8*1080P/16*1080P(EAVS-2116)			
 1 pc remote controller 1pc power	◎Adopts H.264 main profile compress standard. lower stream,high image quality. ◎HDMI(1920X1080),VGA(1280X1024), CVBS for output. ◎TCP/IP, DHCP, DDNS, PPPoE for output method. ◎ONVIF for network protocol. ◎Remote monitor playback, PTZ control, Menu control, parameter settings. ◎Motion detection,professional detector with dual identification, privacy protection. ◎IP filtration, Multiple identification,multiple IP backup and grading transmission. ◎6 groups of dayparting color auto switch, video text side parting transmission, P2P and fixed IP directional transmission. ◎IOS/Andriod for phone browse	433/868 (TCP/IP+PSTN)	EAVS GPRS MODULE	
EAVS-2116 (16CH) Hi 3531	◎Support cloud-based technology,low intelligence analysis.			
 1 pc remote controller 1pcs power		433/868 (TCP/IP+PSTN)	EAVS GPRS MODULE	
	EAVS KEYPAD	*		
	FC-7601 Bus zone expand module	*		






ITEM	Description	Payment Term								
		Package info								
MCB-100 (100M)	Outdoor Perimeter Microwave Barrier With Detection Range About 100M									
	Outdoor Perimeter Microwave Barrier With Detection Range About 150M Detection range up to 200m Power input:10.2-30vdc Detection human intruders walking,running or crawling Quick and easy installation on pole, fence or wall									
MCB-150 (150M)	High RFI/EMI immunity									
	Protection form:direct sunlight, wind up to 30m/sec, snow and rain precipitation(up to 30mm/hour),small animals, ground swing, snow and grass up to 0.3m. making alarm when human intruders walking, running or crawling with speed from 0.1 till 10m/s, applying 5-30volts from control unit to the terminal marked.									
PB-201D MW debugging bo										
										
ABT (LED display)	ABT Series 2 Beams Digital Active Infrared Detector With 8 Channel Frequency Conversion									
	<table border="1"> <tr> <td>ABT-30F</td> <td>Outdoor=50m</td> </tr> <tr> <td>ABT-60F</td> <td>Outdoor=80m</td> </tr> <tr> <td>ABT-80F</td> <td>Outdoor=100m</td> </tr> <tr> <td>ABT-100F</td> <td>Outdoor=120m</td> </tr> </table>	ABT-30F	Outdoor=50m	ABT-60F	Outdoor=80m	ABT-80F	Outdoor=100m	ABT-100F	Outdoor=120m	© Working Voltage: AC/8- © Consumption<2.5W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100
ABT-30F	Outdoor=50m									
ABT-60F	Outdoor=80m									
ABT-80F	Outdoor=100m									
ABT-100F	Outdoor=120m									
ABE (LED display)	ABE Series 3 Beams Digital Active Infrared Detector With 8 Channel Frequency Conversion									
	<table border="1"> <tr> <td>ABE-100</td> <td>Outdoor=150m</td> </tr> <tr> <td>ABE-150</td> <td>Outdoor=200m</td> </tr> <tr> <td>ABE-200</td> <td>Outdoor=250m</td> </tr> <tr> <td>ABE-250</td> <td>Outdoor=300m</td> </tr> </table>	ABE-100	Outdoor=150m	ABE-150	Outdoor=200m	ABE-200	Outdoor=250m	ABE-250	Outdoor=300m	© Working Voltage: AC/8- © Consumption<2W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100
ABE-100	Outdoor=150m									
ABE-150	Outdoor=200m									
ABE-200	Outdoor=250m									
ABE-250	Outdoor=300m									
AX	AX Series 2 Beams Digital Active Infrared Detector With 8 Channel Frequency Conversion									
	<table border="1"> <tr> <td>AX-30</td> <td>Outdoor=30m</td> </tr> <tr> <td>AX-60</td> <td>Outdoor=60m</td> </tr> <tr> <td>AX-80</td> <td>Outdoor=80m</td> </tr> <tr> <td>AX-100</td> <td>Outdoor=100m</td> </tr> </table>	AX-30	Outdoor=30m	AX-60	Outdoor=60m	AX-80	Outdoor=80m	AX-100	Outdoor=100m	© Working Voltage: AC/8- © Consumption<2W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100
AX-30	Outdoor=30m									
AX-60	Outdoor=60m									
AX-80	Outdoor=80m									
AX-100	Outdoor=100m									
AX (LED display)	AX Series 2 Beams Digital Active Infrared Detector With 8 Channel Frequency Conversion									
	<table border="1"> <tr> <td>AX-30A</td> <td>Outdoor=30m</td> </tr> <tr> <td>AX-60A</td> <td>Outdoor=60m</td> </tr> <tr> <td>AX-80A</td> <td>Outdoor=80m</td> </tr> <tr> <td>AX-100A</td> <td>Outdoor=100m</td> </tr> </table>	AX-30A	Outdoor=30m	AX-60A	Outdoor=60m	AX-80A	Outdoor=80m	AX-100A	Outdoor=100m	© Working Voltage: AC/8- © Consumption<2W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100
AX-30A	Outdoor=30m									
AX-60A	Outdoor=60m									
AX-80A	Outdoor=80m									
AX-100A	Outdoor=100m									
ABH (LED display)	ABH Series 4 Beams Digital Active Infrared Detector With 8 Channel Frequency Conversion									
	<table border="1"> <tr> <td>ABH-100F</td> <td>Outdoor=150m</td> </tr> <tr> <td>ABH-150F</td> <td>Outdoor=200m</td> </tr> <tr> <td>ABH-200F</td> <td>Outdoor=250m</td> </tr> <tr> <td>ABH-250F</td> <td>Outdoor=300m</td> </tr> </table>	ABH-100F	Outdoor=150m	ABH-150F	Outdoor=200m	ABH-200F	Outdoor=250m	ABH-250F	Outdoor=300m	© Working Voltage: AC/8- © Consumption<3W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100
ABH-100F	Outdoor=150m									
ABH-150F	Outdoor=200m									
ABH-200F	Outdoor=250m									
ABH-250F	Outdoor=300m									

ITEM			Description		
ABL (LED display)	ABH Series 6 Beams Digital Active Infrared Detector With 8 Channel Frequency Conversion				
	ABL-50F	Outdoor=50m	© Working Voltage: AC/8- © Consumption<4W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100		
	ABL-100F	Outdoor=100m			
	ABL-150F	Outdoor=150m			
	ABL-200F	Outdoor=200m			
	ABL-250F	Outdoor=250m			
ABI	Dual Way Communication 6 Beams Digital Active Infrared Detector				
	ABI-606A	Outdoor=60m	*Height 160/200cm *Alarm light and venetian options *remote arm/disarm by the remote controller *working voltage:AC220V	Alarm Light	
					Venetian Light
	ABI-1006A	Outdoor=100m		Alarm Light	
				Venetian Light	
	Dual Way Communication 6 Beams Digital Active Infrared Detector + Microwave Technology				
	ABI-606B	Outdoor=60m	*DUAL MW+PIR *Height 160/200cm *Alarm light and venetian options *remote arm/disarm by the remote controller *working voltage:AC220V DC/10-36V	Alarm Light	
					Venetian Light
	ABI-1006B	Outdoor=100m		Alarm Light	
				Venetian Light	
	Dual Way Communication 8 Beams Digital Active Infrared Detector				
ABI-608A	Outdoor=60m	*Height 160/200cm *Alarm light and venetian options *remote arm/disarm by the remote controller *working voltage:AC220V	Alarm Light		
				Venetian Light	
ABI-1008A	Outdoor=100m		Alarm Light		
			Venetian Light		
Dual Way Communication 8 Beams Digital Active Infrared Detector + Microwave Technology					
ABI-608B	Outdoor=60m	*DUAL MW+PIR *Height 160/200cm *Alarm light and venetian options	Alarm Light		
				Venetian Light	
ABI-1008B	Outdoor=100m	*remote arm/disarm by the remote controller *working voltage:AC220V DC/10-36V	Alarm Light		
			Venetian Light		


ITEM	Description					
ABX	ABX Series 4 Beams Wireless Active Infrared Detector					
	ABX-104 Outdoor:10m	© Working Voltage: AC/8-20V DC/10-36V © Consumption<2.5W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100 © Height:80cm				
	ABX-204 Outdoor:20m			ABX-404 Outdoor:50m	ABX-604 Outdoor:60m	
	ABX Series 6 Beams Wireless Active Infrared Detector					
	ABX-106 Outdoor:10m			© Working Voltage: AC/8-20V DC/10-36V © Consumption<2.5W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100 © Height:105cm		
	ABX-206 Outdoor:20m	ABX-406 Outdoor:40m	ABX-606 Outdoor:60m			
	ABX Series 8 Beams Wireless Active Infrared Detector					
	ABX-108 Outdoor:10m	© Working Voltage: AC/8-20V DC/10-36V © Consumption<2.5W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100 © Height:105cm				
	ABX-208 Outdoor:20m			ABX-408 Outdoor:40m	ABX-608 Outdoor:60m	
	ABX Series 10 Beams Wireless Active Infrared Detector					
	ABX			ABX Series 10 Beams Wireless Active Infrared Detector		
		ABX-1010 Outdoor:10m	© Working Voltage: AC/8-20V DC/10-36V © Consumption<2.5W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100 © Height:105cm			
		ABX-2010 Outdoor:20m			ABX-4010 Outdoor:40m	ABX-6010 Outdoor:60m
		ABX Series 12 Beams Wireless Active Infrared Detector				
ABX-1012 Outdoor>25m Indoor>75m		© Working Voltage: AC/8-20V DC/10-36V © Consumption<2.5W © Alarm Port: DC30/100 © Anti Mist Output: DC30/10 © Tamper Output: DC30/100 © Height:105cm				
ABX-2012 Outdoor>25m Indoor>75m				ABX-4012 Outdoor>50m Indoor>150m	ABX-6012 Outdoor>75m Indoor>225m	

ITEM	PHOTO	Description	Frequency
Wireless Temperature And Heat Detector With LCD Display			
MD-240R		Wireless Temperature And Heat Detector With LCD Display Wireless fire alarm, heat detector,2x1.5V AA	433
Wireless Electrochemical CO sensor With LCD Display			
MD-2001R		Wireless Electrochemical CO sensor With LCD Display * Electrochemical Co detector * Power Supply: 2x1.5V AA * Digital LCD Display * 5 year Sensor L	433
Wireless Glass break detector			
FG-2036R		Wireless Glass break detector * Adjustable sensitivity: high, medium,low, minimum * Power Supply: 2 x 3V CR123 Lithiumbattery	433
Wireless indoor PIR			
MC-435R DMT		Wireless indoor PIR Wireless PIR detector Pet immunity 3xAAA size alkaline battery	433
Outdoor PIR			
FT-89RS Solar power		Wireless Outdoor Solar Detector(PIR+MW) Wireless and wired Solar powerdetector, used for outdoor,two reliable outer case, anti-rain. IP65Dual infrared+ dual Microwave/Frensallensbuilt-in 7.4V/1000mA rechargeableLithium battery, battery can last 2months when full charge	433/868
FT-89R		Wireless Outdoor Detector(PIR+MW) Dual PIR+2 MW with way recognition technology Adopts self designed MASK chip with DMT technology. With look down window to avoid blind corner and weatherproof design. Detection distance:15M With built-in lithium rechargeable backup battery	433/868
Curtain style PIR(For Window/door use)			
MD-448R DMT		Adopts curtain style FRESNEL lens. Optional intrusion direction Low power consumption, built-in 2xAA batteries. Detection range:6M Detection angle:20	433/868


ITEM	PHOTO	Description	Frequency
Ceiling mount PIR			
MC-7380R DMT		Adoptsqquad pyroelectric infrared sensor and plane antenna MW emitter Adopts self-designed MASK chip with DMT technology. Low power consumption, built-in 2xAAA batteries. Detection range:10M Detection angle:360	433/868
Wall mount PIR			
MC-8250R DMT		Wireless PIR Detector Adopts self designed MASK chip with DMT technology. Reliable detection performance with 2 independent quad PIR technology. Excellent false alarm prevention with look down window to avoid blind corn Detection range:12M Detection angle:110	433/868
MC-335R DMT		Wireless PIR Detector Anti white light with spherical lens and sealed optical design Adopts self desgined MASK chip with DMT technology Detection distance:9M Detection angle:110 Wireless PIR Detector Adopts MW&PIR technology, dual-processor	433/868
DT-335R		Wireless PIR Detector Anti white light with spherical lens and sealed optical design Adopts self desgined MASK chip with DMT technology Detection distance:9M Detection angle:110 Wireless PIR/MW Detector Adopts MW&PIR technology, dual-processor	433
MC-355R DMT		Wireless PIR Detector Anti white light with spherical lens and sealed optical design. Adopts self desgined MASK chip with DMT technology Detection distance:9M Detection angle:110	433
MC-55R DMT		Wireless PIR Detector Adopts self designed MASK chip with DMT technology Patented Multi-code wireless code. Detection distance:12M Detection angle:110	433
DT-55R DMT		Wireless Dual PIR Detector Adopts self design MASK chip with DMT technology Adopts MW&PIR technology dual processor With AAA battery 3pcs. Detection distance:10M Detection angle:110	433








ITEM	PHOTO	Description	Frequency
MC-235R DMT		Wireless PIR Detector Column lens, sensitive 3D column optical design. Random dynamic time segmentation DMT technology. With AAA battery 3pcs. Detection distance:6M Detection angle:110	433
PE-81R DMT		Wireless PIR+WM Detector Adopts MW&PIR technology, dual processor. Excellent false alarm prevention with look down window to avoid blind corner Detection range:12M Detection angle:110	433
DT-81R DMT		Wireless PIR+WM Detector Adopts MW&PIR technology, dual processor. Excellent false alarm prevention with look down window to avoid blind corner Detection range:12M Detection angle:110	868
MC-760R DMT		Sealed optical design Random dynamic time segmentation DMT technology. Dual infrared FRESNEL lens, with look down zone to avoid blind corner. Detection range:6M Detection angle:110	433
DT-8250R		Wireless PIR Detector Adopts self designed MASK chip with DMT technology. Reliable detection performance with 2 independent quad PIR technology. Excellent false alarm prevention with look down window to avoid blind corner Detection range:12M Detection angle:110	433








Wireless Gas Detector; Gas detected: coal gas ,natural gas ,LPG (liquefied petroleum gas)
Alarm density: gas - 0.1~0.5% / natural gas - 0.1~0.3% / LPG - 0.1~0.5% Alarm time around 3 minutes / built-in siren





MD-2000R		Wireless Gas Detector(LGP) Wireless Gas detector , built-in transformer, with DC 12V/1A power adaptor	433/868
----------	-------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------	---------

Wireless Smoke Detector(433mhz/868mhz)/Fireproof Alarm System

MD2100R		Wireless Smoke detector built-in 2XCR123A 3.0V/1300mA lithium battery smog sensitivity complies with U1217,3.2% feet; built-in buzzer make sound in each 2 hours when battery low	433/868
---------	-------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------











ITEM	PHOTO	Description	Frequency
Wireless Emergency Button			
PB-200R		Wireless emergency button, built-in 1pc 23A12V alkaline battery	433/868
PB-201R		Keyfob wireless emergency button, built-in 1pc 3.0V CR2032 lithium battery	433
Wireless Remote Controller			
PB-433R		Wireless 4-Key Slide Remote Control, built-in 2pcs 3.0V CR2032 lithium battery	433
PB-403R		Wireless 6-Key Remote Control, built-in 2pcs 3.0V CR2032 lithium battery	433/868
Wireless to Wireless(wireless distance repeater)			
PB-205R		Wireless repeater(wireless range expanded)built-in rechargeable battery backup with power adaptor 12V/1000mA	433
PB-204R		Wireless repeater, 868mhz	868
FC-008R		Wireless to wired converter, Max 8 wireless device	433/868
Wireless doorbell			
PB-206R		Wireless doorbell, built-in 1pc 23A 12V alkaline battery	433/868
TWO-WAY communication Wireless keypad			
PB-500R LCD		TWO WAY LCD wireless keypad Built-in 4pcs AAA size alkaline bat	433
PB-502R LCD		Two way LCD wireless keypad Built-in backup lithium battery, with	433/868











ITEM	PHOTO	Description	Frequency
Wireless water leakage detector			
MD-230R		Wireless water leakage detector 1xCR123A 3.0V/1300mA lithium battery	433/868
Wireless siren for indoor and balcony use			
MD-204R		Wireless sound only Siren 110db for indoor use Built-in rechargeable battery with power adaptor 12V	433
MD-214R		Wireless siren with flashing light for outdoor use 110db Built-in 7.4V/850mAh rechargeable lithium battery (available in red and blue color) with power adaptor 12V/1000mA	433/868
Wireless siren for Outdoor use, two-way communication to alarm panel(433mhz/868mhz)			
MD-325R NEW		Wireless Outdoor Siren Wireless flash light siren Built-in 6V Alkaline 4xD size battery	868
MD-334R		Wireless Outdoor Siren Standby current: ≤220ua Receiving distance: ≥60 Volume: 110db@ 1M Alarm current: ≤1.2A Internal power supply: 12v rechargeable battery	433/868
MD-326R		Wireless Solar Outdoor Siren Standby current: ≤220ua Receiving distance: ≥60 Volume: 110db@ 1M Alarm current: ≤1.2A Internal power supply: 12v/1.2mA	433/868
MD-313R NEW		Wireless Siren Wireless flash light siren, Built-in 4.5V Alkaline 3xD size battery	868










ITEM	PHOTO	Description	Frequency
WIRELESS VIBRATION SENSOR			
MD-2018R		Wireless vibration detector Built-in 3.0V CR2032 lithium battery 4-level sensitivity adjustable	433/868
WIRELESS MAGNETIC CONTACT			
MD-209R		Wireless Magnetic Door contact 3xAAA size alkaline battery	433
MD-210R		Wireless Magnetic Door contact 1xCR123A 3.0V/1300mA lithium battery	433/868
MD-215R		Wireless Magnetic Door contact Built-in 3.0V CR2032 lithium battery	433/868
MD-212R		Wireless roll gate magnetic detector 1xCR123A 3.0V/1300mA lithium battery	433/868
BATTERY FOR PIR AND PANEL			
CR123A		3V lithium battery	*
12V/7A		12V/7A lead acid battery	*





Detector remarks

MC--PIR ONLY; MD-WITH DIRECTION RECOGNITION; DT-DUAL TECH(PIR & MW); ODT-DUAL TECH FOR OUTDOOR
ALL THE WIRELESS ACCESSORIES ARE COMPATIBLE WITH THE CONTROL PANELS

ITEM	Description
Wired Outdoor PIR	
FT-89	
	<p>1, Wired detector, used for outdoor, tworeliable outer case, anti-rain 2, Pet-immune and anti-mask function, Dual-tech(dual PIR+dual MW) 3, Dimensions:218mm×110mm×118mm</p>
DG-85	
	<p>Wired Outdoor Digital PIR Detector WithHigh Accuracy,IP65; dual PIR+Intel.Coverage up to 12*12m.</p>
FT-85	
	<p>Wired dual-tech Outdoor Digital PIRDetector With High Accuracy, IP65dual PIR+MW;coverage up to 12*12</p>
ODT-8350	
	<p>Wired dual-tech Outdoor Digital PIR,dual Microave , Detector Pet immunity ,IP65coverage up to 12*12m</p>
ODT-8250DMT	
	<p>Wired dual-tech Outdoor Digital PIR,dual Microave , Detector Pet immunity ,IP65coverage up to 12*12m</p>
Wired Indoor Curtain Style PIR	
DDP-968	
	<p>Wired curtain style PIR+Microwavedetector</p>
MD-442DMT	
	<p>Wired curtain style PIR with intrusiondirection recognition, intrusion directionadjustable Pet immunityDimensions:86×86×50mm</p>
MD-448DMT	
	<p>Wired curtain style PIR with intrusiondirection recognition, intrusion directionadjustable Pet immunityDimensions:90mm×50mm×40mm</p>
Wired Ceiling Mount PIR	
DT-7380	
	<p>Wired Dual-tech ceiling mount sensorCoverage up to 10m diameterDimensions:φ110×40mm</p>
MX-720T	
	<p>Wired ceiling mount PIRWith selectable pulse count Dimensions:Φ86×25mm</p>

ITEM	Description
Wired Wall Mount PIR	
MC-800DMT	
	Wired PIR Pet immunity coverage up to 12*12m
MC-435DMT	
	Wired PIR Pet immunity coverage up to 12*12m
MC-8250DMT	
	Wired PIR Pet immunity coverage up to 12*12m
DT-8250DMT	
	Wired dual-tech detector, PIR+MW Anti-cloak coverage up to 12*12m
MC-215	
	Wired PIR, with "true motion recognition" with Look-down viewfinder to avoid blind corner
DT-700	
	Wired dual-tech detector, PIR+MW Anti-cloak Pet immunity
DT-7425	
	Wired dual-tech detector, PIR+MW Anti-cloak coverage up to 12*12m
Wired Gas/Smoke detector	
MD-2006	
	Wired smoke detector smog sensitivity: In comply with U1217,3.2%/feet Alarm volume: 85db at 10feet
MD-2206	
	Wired gas detector Alarm concentration: Coal Gas: 0.1 ~ 0.5%LEL Natural ga: 0.1 ~ 0.3%LEL LPG: 0.1 ~ 0.5% LEL Alarm volume: 85db at 10feet
FG-2036	
	Ceiling mount wired glass break detector

ITEM	Description
Wired siren	
MD-204 	Standby current:300mA Receiving distance:≥60 Volume:108db@ 1M Alarm current:≤1.2A
MD-214 	Wired Siren with flashing light, tamperswitch (available in red and blue color)
MD-205 	Wired sound only Siren
Wired siren For Outdoor use	
MD-325 HOT 	Wired Siren with flashing light, tamperswitch. Size:30cmx19cmx7cm. Powerfrom 220V/15V DC separately.
Wired emergency button	
PB-200 	Wired emergency button
Wired Magnetic Contact for Door/Window	
MD-134A 	Wired embeded magnetic contactwindow, ABS housing, packing: 20 set or40 set per polybag
MD-138B 	Wired surface mount magnetic contact fordor or window, ABS housing, packing:20 set or 40 set per polybag
MD-136 	Surface mount metal mangetic contactfor door or window
MD-155 	Surface mount metal mangetic contactfor rolling gate

ITEM	Description
Mounting brackets for PIR	
PB-301 	Bracket for wall, ceiling and corner (for FT/DG-85), available color: white/grey
PB-302 	Bracket for wall, ceiling or corner
PB-303 	Bracket for wall and corner
Wired Keypad	
PB-503 Touch keypad 	Two way touch LCD display