



PRODUCT CATALOGUE

Fire Detection Alarms

T H E
W O R L D S
R E L I A B L E
A L A R M S

Contents

Company Profile

Part 1: Photoelectric Smoke Alarm

I) Standalone	
SM01/ SM02 /	1
SM03-1 /	2
SM11-3	3
SM12-1 / SM12-3	4
II) Wireless (Wi-Fi or RF433/868 MHz)	
SM11W-3	5
SM11W	6
SM11R-3	7
SM11R	8

Part 2: Heat Alarm

I) Standalone	
SM11H	9
II) Wireless (Tuya Wi-Fi)	
SM11HW-3	10
SM11HW	1

Part 3: Carbon Monoxide Alarm

I) Standalone	
CO01 White	12

CO01 Black	13
CO0	14
CO02V	1
CO02VW	5
II) Wireless (Tuya Wi-Fi)	
CO02W	1
CO02VW	17

Part 4: Combination Alarm

I) Standalone	
SC01	18
SC01V	19
SH0	2
II) Wireless (Wi-Fi or RF433/868 MHz)	
SC01W	21
SC01R	22
SH01W-3	23
SH01W	2

Part 5: Smart Gas Alarm

Part 6: Smart Magnets Door Sensor

Part 7: Smart Water Alarm




WE ARE VOLCANO

SHENZHEN FIRE SECURITY TECHNOLOGY CO., LTD is a high-tech enterprise, specializing in R&D, manufacture and distribution of fire safety alarms and a leading pioneer in early smoke and carbon monoxide alarms.

Each day, we devote ourselves to providing advanced products to protect people and property from fire and related hazards.

Our continuous commitment to innovation has spurred the highest quality smoke, carbon monoxide and combination alarms produced by cutting-edge technology and outstanding reliability.





OUR PRODUCTS


There are many different types of **Smoke alarm, Heat alarm, CO alarm, Combined alarm, Gas detector, Water detector, etc.** including smart versions which can send alerts to your smartphone.

Sealed battery units have a lifetime of five to ten years, after which the battery will run out and the whole unit will need to be replaced.

Normally a sound from the product prompts you that the battery is running low.

There are also **replaceable battery versions** that require the batteries to be replaced periodically.

Whichever version suits requirements, it is important to regularly test the device to ensure that it is working correctly, this is usually done through the test button on the product itself.





Part 1: Photoelectric Smoke Alarm

In many countries smoke alarms include to the basic equipment of a home or are even required by law. With Volcano smoke detectors, you will always be on the safe side.

SM12

I) Standalone Smoke Alarm

- This product is a smart photoelectric smoke sensor, with ultra-low-power MCU design, **operated by battery only**.
- It is an early warning device, can't detect gas, heat, or fire, nor stop fire or put out fire. It is capable of real-time detecting the presence of smoke.
- Once detect danger of fire smoke, red LED will be ON, and alarming to alert you and your family timely.
- It can be **widely used** in household, lounge, coffee house, dancing hall, and any other places need fire alarm monitoring.





Model No.: SM01 / SM02 / SM03 Standalone Mini 10-year Smoke Alarm



1-Year
Warranty



10-Year
Built-in Battery



100% Test



Environmentally
friendly

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |

Product Specifications

Battery Type:	DC 3V (CR123A), Lithium Battery
Battery Life:	10 years life
Operation Current:	< 6 uA (standby); < 50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Alarm Sensitivity:	0.09 - 0.17 dB/m
Low Battery:	2.45 ± 0.05 V
Silence Time:	approx. 10 minutes
Comply to Standard EN14604:2005/AC:2008	





Model No.: SM11-1 / SM11-
2 Standalone Ultra-thin 1-year / 3-year Smoke Alarm



1-Year
Warranty



1-Year
3-Year



100% Test
Replaceable
battery



Environmentally
friendly

SM11-1/SM11-

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |

Product Specifications

- | | |
|---|--|
| Battery Type: | DC 2*1.5V Carbon Zinc battery (R6P)
/ DC 2*1.5V AA Alkaline (LR6、MN1500) |
| Battery Life: | 1 year life / 3 years life |
| Operation Current: | < 10 uA (standby); <70 mA (alarm) |
| Alarm Volume: | > 85 dB(A) at 3 meters |
| Alarm Sensitivity: | 0.09 - 0.17 dB/m |
| Low Battery: | 2.6+/-0.1V |
| Silence Time: | approx. 10 minutes |
| Comply to Standard EN14604:2005/AC:2008 | |





Model No.: SM11

Standalone Ultra-thin 5-year / 10-year Smoke Alarm



1-Year
Warranty



5-Year
10-Year



100% Test
Sealed Battery



Environmentally
friendly

SM11 & 5-year & 10-
year

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |

Product Specifications

Battery Type:	DC 3V, Lithium Battery
Battery Life:	10 years life
Operation Current:	< 10 uA (standby); <70 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Alarm Sensitivity:	0.09 - 0.17 dB/m
Low Battery:	2.6+/-0.1V
Silence Time:	approx. 10 minutes
Comply to Standard EN14604:2005/AC:2008	





Smoke & 1year or 3 years

Model No.: SM12-1 / SM12-3

Standalone Ultra-thin 1-year / 3-year Smoke Alarm



1-Year
Warranty



1-Year
3-Year




100% Test
Replaceable
Battery



Environmentally
friendly

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Product Specifications

Battery Type:	DC 2*1.5V Carbon Zinc battery (R6P) / DC 2*1.5V AA Alkaline (LR6、MN1500)
Battery Life:	1 year life or 3 years life
Operation Current:	< 15 uA (standby); <70 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Alarm Sensitivity:	0.09 - 0.17 dB/m
Low Battery:	2.6 ± 0.1 V
Silence Time:	approx. 10 minutes
Comply to Standard	EN14604:2005/AC:2008
Support for customized services:	10 years battery, 5 years battery

II) Wireless Smoke Alarm (Tuya Wi-Fi)

Tips: You can remotely view that happened via tablet or smartphone, download Tuya/Smart Life App from App Store or Google Play.



Smart Life Tuya App





Smoke & Wi-Fi & 3-
Year

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SM11W-3

Wireless Tuya Wi-fi 3-year Smoke alarm



1-Year
Warranty



3-Year



100% Test
**Replaceable
battery**



Environmentally
friendly

Product Specifications

TUYA APP Control

Battery Type:

DC 2*1.5V AA Alkaline (LR6、MN1500)

Battery Life:

1 year life / 3 years life

Operation Current:

< 10 uA (standby); <70 mA (alarm)

Alarm Volume:

> 85 dB(A) at 3 meters

Alarm Sensitivity:

0.09 - 0.17 dB/m

Low Battery:

2.6+/-0.1V

Silence Time:

approx. 10 minutes

Comply to Standard EN14604:2005/AC:2008



Smoke & Wi-Fi & 10-
Year

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SM11W

Wireless Tuya Wi-fi 10-year Smoke Alarm



1-Year
Warranty



10 Years
Built-in Battery



100% Test




Environmentally
friendly

Product Specifications

Battery Type:	DC 3V (CR123A), Lithium Battery
Battery Life:	5~10 years life
Operation Current:	< 10 uA (standby); <70 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Alarm Sensitivity:	0.09 - 0.17 dB/m
Low Battery:	2.6+/-0.1V
Silence Time:	approx. 10 minutes
Comply to Standard EN14604:2005/AC:2008	





Model No.: SM11R-3

Wireless Interlinked 3-year Smoke Alarm



1-Year
Warranty



3-Year



100% Test
**Replaceable
battery**



Environmentally
friendly



**Remote
Control**

Smoke & Interlinked &
3-Year

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Product Specifications

Battery Type:	DC 2*1.5V AA Alkaline (LR6、MN1500)
Battery Life:	1 year life / 3 years life
Operation Current:	< 10 uA (standby); <70 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Alarm Sensitivity:	0.09 - 0.17 dB/m
Low Battery:	2.6+/-0.1V
Silence Time:	approx. 10 minutes
Radio Frequency:	868MHz / 433 MHz
Comply to Standard EN14604:2005/AC:2008	



Smoke & Interlinked &
3-Year

Packing List

- | | |
|-------------------------------|-----------------|
| 1 × Photoelectric smoke alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SM11R

Wireless Interlinked 10-year Smoke Alarm



1-Year
Warranty



10-Year
Built-in Battery



100% Test



Environmentally
friendly



Remote
Control

Product Specifications

Battery Type:	DC 3V (CR123A), Lithium Battery
Battery Life:	10 years life
Operation Current:	< 10 uA (standby); <70 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Alarm Sensitivity:	0.09 - 0.17 dB/m
Low Battery:	2.6+/-0.1V
Silence Time:	approx. 10 minutes
Radio Frequency:	868MHz / 433 MHz
Comply to Standard EN14604:2005/AC:2008	

Placement of Smoke Detectors

Install smoke alarms inside each bedroom, outside each sleeping area and on every level of the home, including the basement. On levels without bedrooms, install alarms in the living room (or den or family room) or near the stairway to the upper level, or in both locations.



Smoke Alarm

One on every level and in every bedroom



Carbon Monoxide Alarm

One on every level and in every bedroom
kitchen and garage

Part 2 : Heat Alarm

A heat alarm is a safety device designed to **create an alert** when the room in which it's installed reaches a certain temperature.

This can be a better option for areas such as **a kitchen or bathroom** which are more likely to get smoky or steamy, sometimes unnecessarily setting off an alarm designed to detect these elements.

Suitable for **commercial and domestic use**, a heat detector is a legal requirement in some environments. Suitable for use across any room, multiple units can often be linked together for optimum cover throughout the property.

Heat Protection for Kitchen

Volcano heat detectors will detect abnormally high temperatures or rapid rises in temperature and alert you of potential fire in your kitchen.



Heat & Interlinked & 3-Year or 10-year

Packing List

- | | |
|----------------------|-----------------|
| 1 × Heat alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SM11H

Wireless Tuya Wi-fi 3-year/10-year Heat alarm



1-Year
Warranty



3-Year



100% Test
**Replaceable
battery**



Environmentally
friendly

Product Specifications

Battery Type:

DC 2*1.5V AA Alkaline (LR6、MN1500); DC 3V

Battery Life:

3 years life / 10 years

Operation Current:

< 10 uA (standby); <70 mA (alarm)

Alarm Volume:

> 85 dB(A) at 3 meters

Low Battery:

2.6+/-0.1V

Silence Time:

approx. 10 minutes

Heat sensitivity:

54-70°C

Heat Alarm Sound Pattern: BI 0.2s - pause 0.2s – BI 0.2s – pause 0.2s – BI 0.2s – pause 0.2s, with the red LED flash, repeat this alarm pattern.

Comply to Standard EN14604:2005/AC:2008



Heat & Wi-Fi & 3-
Year

Packing List

- | | |
|----------------------|-----------------|
| 1 × Heat alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SM11HW-3

Wireless Tuya Wi-fi 3-year Heat alarm



1-Year
Warranty



3-Year



100% Test
**Replaceable
battery**



Environmentally
friendly

Product Specifications

TUYA APP Control

Battery Type:

DC 2*1.5V AA Alkaline (LR6、MN1500)

Battery Life:

1 year life / 3 years life

Operation Current:

< 10 uA (standby); <70 mA (alarm)

Alarm Volume:

> 85 dB(A) at 3 meters

Low Battery:

2.6+/-0.1V

Silence Time:

approx. 10 minutes

Heat sensitivity:

54-70°C

Heat Alarm Sound Pattern: BI 0.2s – pause 0.2s – BI 0.2s – pause 0.2s – BI 0.2s – pause 0.2s, with the red LED flash, repeat this alarm pattern.

Comply to Standard EN14604:2005/AC:2008



Heat & Wi-Fi & 10-Year

Packing List

- | | |
|----------------------|-----------------|
| 1 × Heat alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SM11HW

Wireless Tuya Wi-fi 10-year Heat Alarm



1-Year
Warranty



10-Year
Built-in Battery



100% Test



Environmentally
friendly

Product Specifications

TUYA APP Control

Battery Type:

DC 3V (CR123A), Lithium Battery

Battery Life:

10 years life

Operation Current:

< 10 uA (standby); < 70 mA (alarm)

Alarm Volume:

> 85 dB(A) at 3 meters

Low Battery:

2.6+/-0.1V

Silence Time:

approx. 10 minutes

Heat sensitivity:

54-70°C

Heat Alarm Sound Pattern: BI 0.2s - pause 0.2s – BI 0.2s – pause 0.2s – BI 0.2s – pause 0.2s, with the red LED flash, repeat this alarm pattern.

Comply to Standard EN14604:2005/AC:2008

Part 3 : Carbon Monoxide Detector

A carbon monoxide detector is a critical and potentially life saving device that sounds an alert if it detects the presence of the odourless, tasteless and colourless gas. It **continuously monitors and measure** the level of CO in the air.



Typical sources of danger include:

Blocked chimneys

If chimneys are blocked, exhaust gases can no longer be sufficiently removed from the residence or house - or at all. Blocked chimneys – due to birds' nests or other garbage – are frequently a reason why people succumb to carbon monoxide poisoning while asleep.

Fireplace, gas stove, oil and gas heating, grills

Devices which run on fossil fuels are an additional source of danger. The scope of fossil fuels includes coal, crude oil and natural gas, which are used in many devices in homes and gardens, such as:

- Fireplaces and stoves
- Gas stoves
- Oil and gas heating systems featuring oil and gas boilers or solid fossil fuels such as wood, coal or pellets, flow heaters
- Wood or electric grills

Facts and figures in Europe*

Country comparison: Deaths after carbon monoxide poisoning

Germany: Around ten deaths p.a.

UK: Around 40 deaths p.a.

Spain: 154 deaths in 2011

Belgium: Around 150 deaths p.a.

Hungary: Around 50 deaths p.a.

Poland: Around 150 deaths p.a.

France: Around 400 deaths p.a.

** Sources: National Health Service/UK,
German Federation of Chimney
Sweepers (ZIV)*



Model No.: CO01 White Carbon Monoxide Detector (3-Year)



1-Year
Warranty



3-Year



100% Test
**Replaceable
Battery**



Environmentally
friendly

Carbon monoxide & 3
years

Packing List

- | | |
|---------------------------|-----------------|
| 1 × Carbon Monoxide alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Product Specifications

Battery Type:	9V Alkaline
Battery Life:	3 years life
Sensor Type:	Electrochemical
CO Sensitivity:	50ppm: 60~90 mins; 100ppm: 10~40 mins; 300ppm: < 3mins
Operation Current:	< 45 uA (standby); <50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Temperature:	4.4°C ~ 37.8°C
Humidity:	10% ~ 95% RH (non-condensing)
Silence Time:	approx. 10 minutes
Comply to Standard	50291: 2010



Carbon monoxide & 3
years

Packing List

- | | |
|---------------------------|-----------------|
| 1 × Carbon Monoxide alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: CO01 Black

Carbon Monoxide Detector (3-Year)



1-Year
Warranty



3-Year



100% Test
Replaceable
Battery



Environmentally
friendly

Product Specifications

Battery Type:	9V Alkaline
Battery Life:	3 years life
Sensor Type:	Electrochemical
CO Sensitivity:	50ppm: 60~90 mins; 100ppm: 10~40 mins; 300ppm: < 3mins
Operation Current:	< 45 uA (standby); <50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Temperature:	4.4°C ~ 37.8°C
Humidity:	10% ~ 95% RH (non-condensing)
Silence Time:	approx. 10 minutes
Comply to Standard	50291: 2010



Carbon monoxide & 3
years

Packing List

- | | |
|---------------------------|-----------------|
| 1 × Carbon Monoxide alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: CO02

Carbon Monoxide Detector (3-Year)



1-Year
Warranty



3-Year



100% Test
Replaceable
Battery



Environmentally
friendly

Product Specifications


Battery Type:	DC 2*1.5V AA Alkaline (LR6、MN1500)
Battery Life:	3 years life
Sensor Type:	Electrochemical
CO Sensitivity:	50ppm: 60~90 mins; 100ppm: 10~40 mins; 300ppm: < 3mins
Operation Current:	< 45 uA (standby); <50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Temperature:	4.4°C ~ 37.8°C
Humidity:	10% ~ 95% RH (non-condensing)
Silence Time:	approx. 10 minutes
Comply to Standard	50291: 2010



Carbon monoxide & voice warning & 3 years

Packing List

- | | |
|---------------------------|-----------------|
| 1 × Carbon Monoxide alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: CO02V

Carbon Monoxide Detector (3-Year) with Voice Warning



1-Year
Warranty



3-Year



100% Test
Replaceable
Battery



Voice Warning

Product Specifications

The voice warning feature will announce either 'FIRE! FIRE!' or 'WARNING! CARBON MONOXIDE' depending on which danger is detected.

DC 2*1.5V AA Alkaline (LR6、MN1500)

Battery Type:

3 years life

Battery Life:

Electrochemical

Sensor Type:

50ppm: 60~90 mins; 100ppm: 10~40 mins;

CO Sensitivity:

300ppm: < 3mins

< 45 uA (standby); <50 mA (alarm)

Operation Current:

> 85 dB(A) at 3 meters

Alarm Volume:

4.4°C ~ 37.8°C

Temperature:

10% ~ 95% RH (non-condensing)

Humidity:

approx. 10 minutes


Silence Time:

Comply to Standard 50291: 2010



Model No.: CO02W


Carbon Monoxide Detector (3-Year)



Carbon monoxide & Tuya Wi-Fi & 3 years

Packing List

- | | |
|---------------------------|-----------------|
| 1 × Carbon Monoxide alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



1-Year
Warranty



3-Year



100% Test
Replaceable
Battery



Environmentally
friendly

Product Specifications

TUYA APP Control	802.11 b/g/n
Battery Type:	DC 2*1.5V AA Alkaline (LR6、MN1500)
Battery Life:	3 years life
Sensor Type:	Electrochemical
CO Sensitivity:	50ppm: 60~90 mins; 100ppm: 10~40 mins; 300ppm: < 3mins
Operation Current:	< 45 uA (standby); <50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Temperature:	4.4°C ~ 37.8°C
Humidity:	10% ~ 95% RH (non-condensing)
Silence Time:	approx. 10 minutes
Comply to Standard 50291: 2010	

Model No.: CO02VW


Carbon Monoxide Detector (3-Year) with Voice Warning



Carbon monoxide & voice warning & Tuya Wi-Fi & 3 years

Packing List

- | | |
|---------------------------|-----------------|
| 1 × Carbon Monoxide alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



1-Year
Warranty



3-Year



100% Test
Replaceable
Battery



Voice Warning

Product Specifications

The voice warning feature will announce either 'FIRE! FIRE!' or 'WARNING! CARBON MONOXIDE' depending on which danger is detected.

TUYA APP Control:

Battery Type:

Battery Life:

Sensor Type:

CO Sensitivity:

802.11 b/g/n

DC 2*1.5V AA Alkaline (LR6、MN1500)

3 years life

Electrochemical

50ppm: 60~90 mins; 100ppm: 10~40 mins;

300ppm: < 3mins

< 45 uA (standby); <50 mA (alarm)

Operation Current:

Alarm Volume:

Temperature:

Humidity:

Silence Time:

> 85 dB(A) at 3 meters

4.4°C ~ 37.8°C

10% ~ 95% RH (non-condensing)

approx. 10 minutes

Comply to Standard EN50291: 2010

Part 4: Combination Detector

2-in-1 Protection


- **The combined optical smoke and carbon monoxide (CO) alarm** from Volcano is designed to provide audible and visual warning of both dangers within a single alarm.
- **The smoke heat detector combines** the measurement of the optical smoke alarm with a precise analysis of the temperature change in a room. The smoke heat detector can therefore also be used in the kitchen.



Combo & 1 year or 3 years

Packing List

- | | |
|----------------------|-----------------|
| 1 × Combo alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SC01

Combination Carbon Monoxide and Smoke Alarm



**2 IN 1
Combo Alarm**



**1-Year
3-Year**



**100% Test
Replaceable
Battery**



**Environmentally
friendly**

Product Specifications

Battery Type:	DC 2*1.5V Carbon Zinc battery (R6P) / DC 2*1.5V AA Alkaline (LR6、MN1500)
Battery Life:	1 year life or 3 years life
Sensor Type:	Photoelectronic & Electrochemical
CO Sensitivity:	50ppm: 60~90 mins; 100ppm: 10~40 mins; 300ppm: < 3mins
Alarm Sensitivity:	0.09 - 0.17 dB/m
Operation Current:	< 45 uA (standby); <50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Low Battery:	2.6 ± 0.1 V
Silence Time:	approx. 10 minutes
Comply to Standard EN14604:2005/AC:2008 & 50291: 2010	



Combo& voice warning & 1 year or 3 years

Packing List

- | | |
|----------------------|-----------------|
| 1 × Combo alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SC01V

Combination Carbon Monoxide and Smoke Alarm

with Voice Warning



2 IN 1
Combo Alarm



1-Year
3-Year



100% Test
Replaceable
Battery



Voice Warning

Product Specifications

The voice warning feature will announce either 'FIRE! FIRE!' or 'WARNING! CARBON MONOXIDE' depending on which danger is detected.

Battery Type:

DC 2*1.5V Carbon Zinc battery (R6P)
/ DC 2*1.5V AA Alkaline (LR6、MN1500)

Battery Life:

1 year life or 3 years life

Sensor Type:

Photoelectronic & Electrochemical

CO Sensitivity:

50ppm: 60~90 mins; 100ppm: 10~40 mins;

300ppm: < 3mins

0.09 - 0.17 dB/m

Alarm Sensitivity:

< 45 uA (standby); < 50 mA (alarm)

Operation Current:

> 85 dB(A) at 3 meters

Alarm Volume:

2.6 ± 0.1 V

Low Battery:

approx. 10 minutes

Silence Time:

Comply to Standard EN14604:2005/AC:2008 & 50291: 2010

Model No.: SC01W


Wireless TUYA WI-FI Combination Carbon Monoxide and Smoke Alarm



Combo & TUYA WIFI & 3 years

Packing List

- | | |
|----------------------|-----------------|
| 1 × Combo alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



**2 IN 1
Combo Alarm**



3-Year



**100% Test
Replaceable
Battery**



**Environmentally
friendly**


Product Specifications

Battery Type:	DC 2*1.5V AA Alkaline (LR6、MN1500)
Battery Life:	3 years life
Sensor Type:	Photoelectronic & Electrochemical
CO Sensitivity:	50ppm: 60~90 mins; 100ppm: 10~40 mins; 300ppm: < 3mins
Alarm Sensitivity:	0.09 - 0.17 dB/m
Operation Current:	< 45 uA (standby); <50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Low Battery:	2.6 ± 0.1 V
Silence Time:	approx. 10 minutes
Comply to Standard EN14604:2005/AC:2008 & 50291: 2010	



Packing List

- | | |
|----------------------|-----------------|
| 1 × Combo alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SC01R

Wireless RF 868MHz / 433 MHz Combination Carbon Monoxide and Smoke Alarm



**2 IN 1
Combo Alarm**



3-Year



**100% Test
Replaceable
Battery**



**Environmentally
friendly**

Product Specifications

Battery Type:	DC 2*1.5V AA Alkaline (LR6、MN1500)
Battery Life:	3 years life
Sensor Type:	Photoelectronic & Electrochemical
Radio Frequency:	Combo & RF 868MHz / 433 MHz & 3 years
CO Sensitivity:	50ppm: 60~90 mins; 100ppm: 10~40 mins; 300ppm: < 3mins
Alarm Sensitivity:	0.09 - 0.17 dB/m
Operation Current:	< 45 uA (standby); <50 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Low Battery:	2.6 ± 0.1 V
Silence Time:	approx. 10 minutes
Comply to Standard EN14604:2005/AC:2008 & 50291: 2010	



Combo smoke and heat & 3 years

Model No.: SH01

3-year Smoke and Heat Combined Alarm



**2 IN 1
Combo Alarm**



3-Year



**100% Test
Replaceable
battery**



**Environmentally
friendly**

Product Specifications

Battery Type: **DC 2*1.5V** AA Alkaline (LR6、MN1500)

Battery Life: **3 years life**

Operation Current: < 10 uA (standby); <70 mA (alarm)

Alarm Volume: > 85 dB(A) at 3 meters

Alarm Sensitivity: 0.09 - 0.17 dB/m

Low Battery: 2.6+/-0.1V

Silence Time: approx. 10 minutes

Heat sensitivity: 54-70°C

Heat Alarm Sound Pattern: BI 0.2s - pause 0.2s – BI 0.2s – pause 0.2s – BI 0.2s – pause 0.2s, with the red LED flash, repeat this alarm pattern.

Smoke Alarm Sound Pattern: BI 0.5s - pause 0.5s – BI 0.5s – pause 0.5s – BI 0.5s – pause 1.5s, with the red LED flash, repeat this alarm pattern.

Comply to Standard EN14604:2005/AC:2008

Packing List

1 × Combo alarm

1 × Mounting bracket

1 × Screw Kit

1 × User manual





Combo & Wi-Fi & 3 years

Packing List

- | | |
|----------------------|-----------------|
| 1 × Combo alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SH01W-3

Tuya Wi-fi 3-year Smoke and Heat Combined Alarm



**2 IN 1
Combo Alarm**



3-Year



**100% Test
Replaceable
battery**



**Environmentally
friendly**

Product Specifications

Battery Type: **DC 2*1.5V** AA Alkaline (LR6、MN1500)

Battery Life: **3 years life**

Operation Current: < 10 uA (standby); <70 mA (alarm)

Alarm Volume: > 85 dB(A) at 3 meters

Alarm Sensitivity: 0.09 - 0.17 dB/m

Low Battery: 2.6+/-0.1V

Silence Time: approx. 10 minutes

Heat sensitivity: 54-70°C

Heat Alarm Sound Pattern: BI 0.2s - pause 0.2s - BI 0.2s - pause 0.2s - BI 0.2s - pause 0.2s, with the red LED flash, repeat this alarm pattern.

Smoke Alarm Sound Pattern: BI 0.5s - pause 0.5s - BI 0.5s - pause 0.5s - BI 0.5s - pause 1.5s, with the red LED flash, repeat this alarm pattern.

Comply to Standard EN14604:2005/AC:2008



Combo & Wi-Fi & 10 years

Packing List

- | | |
|----------------------|-----------------|
| 1 × Combo alarm | 1 × Screw Kit |
| 1 × Mounting bracket | 1 × User manual |



Model No.: SH01W

Wireless Tuya Wi-fi 10-year Smoke and Heat Combined Alarm



**2 IN 1
Combo Alarm**



**10-Year
Built-in Battery**



100% Test



**Environmentally
friendly**

Product Specifications

Battery Type:	DC 3V (CR123A), Lithium Battery
Battery Life:	10 years life
Operation Current:	< 10 uA (standby); <70 mA (alarm)
Alarm Volume:	> 85 dB(A) at 3 meters
Alarm Sensitivity:	0.09 - 0.17 dB/m
Low Battery:	2.6+/-0.1V
Silence Time:	approx. 10 minutes
Heat sensitivity:	54-70°C
Heat Alarm Sound Pattern: BI 0.2s - pause 0.2s – BI 0.2s – pause 0.2s – BI 0.2s – pause 0.2s, with the red LED flash, repeat this alarm pattern.	
Smoke Alarm Sound Pattern: BI 0.5s - pause 0.5s – BI 0.5s – pause 0.5s – BI 0.5s – pause 1.5s, with the red LED flash, repeat this alarm pattern.	

Part 5: Wireless Tuya Wi-Fi Gas Detector

WiFi flammable gas alarm, which is used to detect the leakage of flammable gas and prevent the damage caused by gas leaks. This product is used indoors where leakage may occur, such as kitchen.





Gas & Wi-Fi & AC

Model No.: RQ400A

Wireless TUYA WIFI GAS Detector (CH4)



1-Year
Warranty



AC 85V ~
250V



100% Test
Replaceable
Battery



Environmentally
friendly

Product Specifications

TUYA APP Control

Power:

Plugs Support:

Average Consumption:

Alarm Volume:

Alarm Density:

Working Temperature:

Working Humidity:

Comply to CE Standard

802.11 b/g/n

AC 85V ~ 250V

EU / UK / US

≤ 1.5 W

> 85 dB(A) at 3 meters

6% LEL ± 3% LEL (CH4)


-10 ~ 50°C

Max 95% RH

Packing List

1 × Gas Detector

1 × User manual



Part 6: Smart Magnets Door Sensor

Peace of mind from the palm of your hand
You'll know instantly if there's movement at home, or if a window or door opens or closes. And by pairing your sensor with other Hive products, you can also make your home come to life around you.





Door & Wi-Fi & AC

Packing List

- 1 × Magnets Door Sensor
- 1 × User manual
- 1 × Screw Kit



Model No.: DY-MC400A

Wireless TUYA WIFI Magnets Door Sensor



1-Year
Warranty



?

100% Test
**Replaceable
Battery**



Environmentally
friendly

Product Specifications

TUYA APP Control	802.11 b/g/n
Battery Type:	DC 3V LR03
Battery Life:	1 year
Sensor Type:	Photoelectronic & Electrochemical
Operation Current:	< 10 uA (standby); <160 mA (alarm)
Magnetic Control Distance:	≥ 15mm
Low Battery:	≤ 2.7V
Working Temperature:	-10 ~ 50°C
Working Humidity:	Max 95% RH
Comply to Standard EN14604:2005/AC:2008 & 50291: 2010	

Part 7: Smart Water Alarm for Leak Detection and Flood Alerts

Help keep your valuable items safe from water damage with Volcano Water Alarms for Leak Detection and Flood Alerts. It is ideal for placing at the bottom of washing machines, water heaters, and toilets, or in basements where there is a worry of flooding. If a unit senses water, it will emit a loud 85-decibel alarm. Each water sensor is splash- and water-resistant and can be placed up to 6 feet away from the alarm unit.

Great for early detection of leaking appliances or external flooding





Water & Wi-Fi & AC

Packing List

1 × Water Detector

1 × User manual



Model No.: SQ400A

Wireless TUYA WIFI Water Detector



1-Year
Warranty



AC 85V ~
250V



100% Test
Replaceable
Battery



Environmentally
friendly

Product Specifications

TUYA APP Control

802.11 b/g/n

Power:

Power :DC3V 2*1.5V AAA LR03

Special Features:

Waterproof

Operation Current:

< 10 uA (standby); <160 mA (alarm)

Magnetic Control Distance:

≥ 15mm

Low Battery:

≤ 2.7V

Working Temperature:

-10 ~ 50°C

Working Humidity:

Max 95% RH

Sensor can be placed up to 6 feet away from alarm unit.

Part 8: OEM

OEM Duo Pack with Color▼
Box



OEM Single Pack with Color Box
OEM 5-Pack with Color Box